

PROLIT COMPACT

FLOOD LIGHTING LED LUMINAIRE



TECHNICAL FEATURES

Body	Aluminium injection moulded body
Diffuser	Anti-glare tempered glass
Rated Power	50 W / 100 W
Light Source	Power LED
Optical Parts	15° - 30° Lens Narrow Angle Reflector Wide Angle Reflector
Input Voltage	220-240 V 50/60 Hz
Driver	50 W model = 54 W / Cos Ø > 0,9 100 W model = 111 ,2W / Cos Ø > 0,9
IP Protection	IP 65
Colour Temper.	Natural White
Installation	Pole, wall, roof, floor mounted

ORDERING INFORMATION

Order No	Description	Product Code	Power cons. (W)	Dimensions (mm) (axbxh)	Weight (kg)
44564	70W - Narrow angle	PR 12*PS60Z-1040PW/C NB	70	244x308x97	5
44565	70W - Wide angle	PR 12*PS60Z-1040PW/C WB	70	244x308x97	5
44566	70W 60°	PR 12*PS60Z-1040PW/C 60 D	70	244x308x97	5

GENERAL FEATURES

- ✦ Energy saving, Long life, Low lumen depreciation
- ✦ Fast, easy and trouble free installation
- ✦ Environmentally with zero carbon emission
- ✦ Maintenance free (except periodic cleaning)

Applications

- ✦ Small Football field
- ✦ Harbor, Open Area
- ✦ Open Car Parking Area
- ✦ Advertising boards

TECHNICAL DRAWING

