

# SIMPLED

LED LIGHTING LUMINAIRE FOR INDUSTRIAL APPLICATIONS



## TECHNICAL FEATURES

<b>Body</b>	Aluminium profile - RAL 9003
<b>Diffuser</b>	Diffuser with narrow beam angle
<b>Rated Power</b>	48 W - 71 W - 95 W - 142 W
<b>Power Cons.</b>	53 W - 79 W - 105 W - 158 W
<b>Light Source</b>	MID POWER LED
<b>Input Voltage</b>	220-240 V 50-60 Hz
<b>IP Protection</b>	IP 65
<b>Colour Temper.</b>	Cool White, Natural White
<b>CRI</b>	min.65 (5700K) / min.70 (4000K)
<b>Lumen</b>	158W= 17116 lm (5700K) / 14818 lm (4000K)
<b>Lumen/W</b>	109 lm/W (5700K) / 94 lm/W (4000K)
<b>Emergency Kit</b>	Available
<b>Dali Dim Comp.</b>	Available
<b>Installation</b>	Surface

## ORDERING INFORMATION

Order No	Description	Product Code	Dimensions (mm) (axbxh)	Power cons. (W)
40540	48 W SIMPLED (4000K)	SMP 12*HP50U-NW/EDF	516 x 130 x 96	53
40544	48 W SIMPLED (5700K)	SMP 12*HP50U-PW/EDF	516 x 130 x 96	53
40541	71 W SIMPLED (4000K)	SMP 18*HP40U-NW/EDF	629 x 130 x 96	79
40545	71 W SIMPLED (5700K)	SMP 18*HP40U-PW/EDF	629 x 130 x 96	79
40542	95 W SIMPLED (4000K)	SMP 24*HP50U-NW/EDF	916 x 130 x 96	105
40546	95 W SIMPLED (5700K)	SMP 24*HP50U-PW/EDF	916 x 130 x 96	105
40543	142 W SIMPLED (4000K)	SMP 36*HP40U-NW/EDF	1216 x 130 x 96	158
40547	142 W SIMPLED (5700K)	SMP 36*HP40U-PW/EDF	1216 x 130 x 96	158

## GENERAL FEATURES

- ✦ Energy-saving
- ✦ Light pollution free
- ✦ Fast,easy and trouble free installation
- ✦ Low lumen depreciation

### Applications

- ✦ Height ceiling
- ✦ Warehouse

## TECHNICAL DRAWING

